

Παγκόσμιος Ηγέτης στο **Ιδανικό** Κλίμα.



Κεντρικά Γραφεία | Ελ. Βενιζέλου 5 'Εκθεση | Αριστείδου 40 & Ελ.Βενιζέλου 3 ΤΚ | 55133 | Καλαμαριά | Θεσσαλονίκη Τ | 2310.440.844 F | 2310.432.868 e-mail: info@klimamichaniki.gr www.klimamichaniki.gr





Compact, effective and quiet

thanks to the new, innovative structure



Triple Detection sensor to quickly detect air pollution

Equipped with a high sensitivity dust sensor that distinguishes small particles such as $PM_{2.5}$ and larger particles of dust and reacts accordingly. Triple detection of dust, $PM_{2.5}$ and odour is provided.

Functions

Dust (PM _{2.5} /dust) and odour sensor lamps	x			
Streamer discharge	x			
Active plasma ion	×			
Electrostatic HEPA filters	x			
Streamer regenerated deodorizing filter	x			
Econo mode	×			
Auto fan mode	x			
Anti-pollen mode	x			
Turbo mode	x			
Child proof lock	x			
Brightness adjustment	x			
Auto restart after power failure				
Stabilizer free	x			







"Allergy UK Seal of Approval reassures the product is efficient at reducing small particles which may include allergens, bacteria and viruses"

Specifications

			MCK	55W
Application				Floor standing type
Applicable room area			m²	41
Dimensions	Unit	HeightxWidthxDepth	mm	700x270x270
Weight	Unit		kg	9.5
Casing	Colour			White
Fan	Type			Multi Blade Fan (Sirocco fan)
		Air purifying Silent/Low/ operation Medium/Turbo	m³/h	54/120/192/330
		Humidifying Silent/Low/ operation Medium/Turbo	m³/h	102/144/192/330
	Air purifying operation	Silent/Low/Medium/Turbo	dBA	19.0/29.0/39.0/53.0
	Humidifying operation	Silent/Low/Medium/Turbo	dBA	25.0/33.0/39.0/53.0
operation	Power input	Silent/L/M/Turbo	kW	0.011/0.014/0.019/0.058
	Humidification	Silent/Low/Medium/Turbo	ml/h	200/240/300/500
	Water tank c	apacity	- 1	2.7
Air purifying operation	Power input	Silent/L/M/Turbo	kW	0.007/0.010/0.017/0.056
Deodorizing method			Flash streamer + Deodorizing catalyst	
Dust collecting method			Electrostatic HEPA filter	
Air filter Type			Polyethylene terephthalate net	
Sign	Item	01		Dust: 3 stages / Odour: 3 stages / Anti-pollen mode / Water supply lamp / Child proof lock lamp / ON/OFF lamp / Streamer lamp / Econo mode / MOIST mode / AUTO FAN mode / PM 2. 5 sensor lamp: 3 stages / Humildity monitor lamp: 5 stages / Humildity setting: Low/Standard/High / Airflow rate: Quiet/Low/Standard/Turbo / Humidity on/off
Power supply	Phase/Frequency/Voltage Hz/V		Hz/V	1~/50/60/220-240/220-230
Туре				Humidifying air purifier

The applicable room area is appropriate for operating the unit of maximum fan speed (HH). Applicable room area indicates the space where a certain amount of dust particles can be remover in 30 minutes. (JEM 1467) | Humidification amount changes in accordance with indoor and outdoor temperature and humidity. Measurement condition: 20°C in temperature, 30% in humidity. | Operating sound levels are the average of values measured at 1m away from the front, left, right and top of the unit. (These are equal to the values in an anechoic chamber) | Electrostatic HEPA filter and humidifying filters are attached in the unit.