



Παγκόσμιος Ηγέτης στο **Ιδανικό** Κλίμα.

Κατάλογος Οικιακών Εφαρμογών



Κεντρικά Γραφεία | Ελ. Βενιζέλου 5
Έκθεση | Αριστείδου 40 & Ελ.Βενιζέλου 3
TK | 55133 | Καλαμαριά | Θεσσαλονίκη
T | 2310.440.844 F | 2310.432.868
e-mail: info@klimamichaniki.gr
www.klimamichaniki.gr



Wall mounted unit

Wall mounted unit, offering good value for money

- › Flat, stylish front panel blends easily within any interior décor and is easier to clean
- NEW** › Voice command via Amazon Alexa or Google Assistant to control main functions such as set point, operation mode, fan speed, etc
- › Daikin residential controller (optional): control your indoor from any location with an app, via your local network or internet
- › Seasonal efficiency values up to A++ in cooling



Efficiency data				FTXC + RXC	20C + 20C	25C + 25C	35C + 35C	50C + 50C	60C + 60C	71C + 71C		
Cooling capacity	Min./Max.		kW		1.3 / 3.0		1.3 / 4.0	1.4 / 6.2	1.8 / 7.0	2.3 / 7.3		
Heating capacity	Min./Max.		kW		1.30 / 4.00		1.30 / 4.80	1.36 / 6.60	1.48 / 8.00	2.30 / 9.00		
Space cooling	Energy efficiency class				A++							
	Capacity	Pdesign	kW	2.08	2.57	3.44	5.08	6.21	6.96			
	SEER			6.89	6.84	6.87	6.45	6.40	5.30			
	η _{s,c}		%	-								
Space heating (Average climate)	Annual energy consumption			kWh/a	106	132	175	276	340	459		
	Energy efficiency class				A+							
	Capacity	Pdesign	kW	1.87	2.23	2.24	3.90	4.10	6.35			
	SCOP/A			4.40	4.45	4.28	4.42	4.24	3.81			
	η _{s,h}		%	-								
Annual energy consumption			kWh/a	594	700	732	1,236	1,354	2,334			
Indoor unit				FTXC	20C	25C	35C	50C	60C	71C		
Dimensions	Unit	HeightxWidthxDepth		mm	288 x 770 x 234				297 x 990 x 273			
Weight	Unit			kg	9.00		9.50		13.0			
Air filter	Type				Removable / washable							
Fan	Air flow rate	Cooling	Silent operation/ Low/Medium/High	m ³ /min	5.4 / 6.5 / 9 / 10.8			7.4 / 8.2 / 10 / 12.2		10.2 / 13.6 / 16 / 20.4		
Sound power level	Cooling			dBA	54		55	57	60			
Sound pressure level	Cooling	Silent operation/Low/High		dBA	20 / 26 / 38		21 / 26 / 39		29 / 33 / 45			
Control systems	Infrared remote control				ARC486A2							
	Wired remote control				-							
Outdoor unit				RXC	20C	25C	35C	50C	60C	71C		
Dimensions	Unit	HeightxWidthxDepth		mm	550 x 658 x 273				615 x 845 x 300		695 x 930 x 350	
Weight	Unit			kg	24.0		26.0		39.0		45.0	
Sound power level	Cooling			dBA	58		60		65		66	
Sound pressure level	Cooling	High		dBA	45		46		51		54	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	10 ~46				-10 ~46			
	Heating	Ambient	Min.~Max.	°CWB					-15 ~18			
Refrigerant	Type				R-32							
	GWP				675.0							
	Charge			kg/TCO ₂ Eq	0.550 / 0.371		0.750 / 0.506		1.00 / 0.675		1.10 / 0.743	1.15 / 0.776
Piping connections	Liquid	OD		mm	6.4							
	Gas	OD		mm	9.52				12.7			
	Piping length OU - IU	Max.		m	20				30			
	System	Chargeless		m	8							
	Additional refrigerant charge			kg/m	0,017 (for piping length exceeding 7.5m)							
	Level difference IU - OU			Max.	15.0				20.0			
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50 / 220-240							
Current - 50Hz	Maximum fuse amps (MFA)			A	16							