

## Τεχνικά Χαρακτηριστικά Split



**ΚΕΝΤΡΙΚΑ ΓΡΑΦΕΙΑ**

Βενιζέλου 5, 55133 Καλαμαριά,  
Θεσσαλονίκη, Τ. 2310 440844

**ΕΚΘΕΣΗ**

Ελευθερίου Βενιζέλου 3 & Αριστείδου  
55133 Καλαμαριά, Θεσσαλονίκη

## Wall mounted unit

Wall mounted unit, offering good value for money

- > Flat, stylish front panel blends easily within any interior décor and is easier to clean
- > Onecta app (optional): control your indoor from any location with an app, via your local network or internet.
- > Seasonal efficiency values up to A++ in cooling
- > Choosing for an R-32 product, reduces the environmental impact with 68% compared to R-410A and leads directly to lower energy consumption thanks to its high energy efficiency



More details and final information can be found by scanning or clicking the QR codes.



FTXC-D



RXC-D

Efficiency data		FTXC + RXC	20D + 20D	25D + 25D	35D + 35D	50D + 50D	60D + 60D	71D + 71D	
Cooling capacity	Min./Max.	kW	1.3/3.0		1.3/4.0	1.4/6.2	1.8/7.0	2.3/7.3	
Heating capacity	Min./Max.	kW	1.30/4.00		1.30/4.80	1.36/6.60	1.48/8.00	2.30/9.00	
Power input	Cooling	Min./Nom./Max.	0.30/0.595/1.15	0.30/0.765/1.15	0.32/1.05/1.74	0.30/1.55/2.11	0.38/1.89/2.05	0.44/2.38/2.54	
	Heating	Min./Nom./Max.	0.28/0.670/1.35	0.28/0.750/1.35	0.28/1.07/1.57	0.27/1.52/1.85	0.33/1.68/2.35	0.50/2.46/2.74	
Space cooling	Energy efficiency class				A++			A++	
	Capacity	Pdesign	kW	2.08	2.57	3.44	5.08	6.21	
	SEER			6.89	6.84	6.87	6.45	6.40	
	Annual energy consumption		kWh/a	106	131	175	276	339	
Space heating (Average climate)	Energy efficiency class				A++			A++	
	Capacity	Pdesign	kW	1.87	2.23	2.24	3.90	4.30	
	SCOP/A			4.40	4.45	4.28	4.42	4.24	
	Annual energy consumption		kWh/a	595	701	733	1,234	1,353	
Nominal efficiency	EER		3.36	3.35		3.29	3.30	2.98	
	COP		3.73	3.79	3.74	3.71	3.81	3.25	
	Energy labeling Directive	Cooling/Heating			A/A			C/C	
Current - 50Hz	Maximum fuse amps (MFA)	A			16				
Indoor unit		FTXC	20D	25D	35D	50D	60D	71D	
Dimensions	Unit HeightxWidthxDepth	mm	288x770x234				297x990x273		
Weight	Unit	kg	9.00		9.50		13.0		
Air filter	Type	Removable / washable							
Fan	Air flow rate	Cooling	5.4/6.1/8.1/10.8		5.4/6.4/8.7/11.1	7.4/8.1/9.9/12.5	10.2/12.5/14.5/20.4		
Sound power level	Cooling	dB(A)	57		58	60	63		
Sound pressure level	Cooling	Silent operation/Low/High	21/26/40		22/26/41	30/33/47	31/38/48		
Control systems	Infrared remote control	ARC486A2							
	Wired remote control	-							
Outdoor unit		RXC	20D	25D	35D	50D	60D	71D	
Dimensions	Unit HeightxWidthxDepth	mm	550x658x273				615x845x300		695x930x350
Weight	Unit	kg	24.0	26.0		39.0		45.0	
Sound power level	Cooling	dB(A)	58		60	65	66	69	
Sound pressure level	Cooling	High	45		46	51	54		
Operation range	Cooling	Ambient	Min.~Max.		10~46		-10~46		
	Heating	Ambient	Min.~Max.		-15~-18				
Refrigerant	Type	R-32							
	GWP	675.0							
	Charge	kg/1000ft <sup>3</sup>	0.550/0.371	0.750/0.506		1.00/0.675	1.10/0.743	1.15/0.776	
Piping connections	Liquid	OD	mm		6.35				
	Gas	OD	mm		9.52		12.7		
	Piping length	OU - IU	Max.		20		30		
	Additional refrigerant charge	System	Chargeless		8				
	Level difference IU - OU	Max.	m		15.0		20.0		
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240						