

ΚΑΘΑΡΙΣΤΕΣ ΑΕΡΑ



ΚΕΝΤΡΙΚΑ ΓΡΑΦΕΙΑ

Βενιζέλου 5, 55133 Καλαμαριά,
Θεσσαλονίκη, Τ. 2310 440844
info@klimamichaniki.gr
www.klimamichaniki.gr

ΕΚΘΕΣΗ

Ελευθερίου Βενιζέλου 3 & Αριστείδου
55133 Καλαμαριά, Θεσσαλονίκη

Intelligent Air Purification, minimalistic design & Humidification MCK70Z



- Onecta App Integration: control indoor air quality with an app, via local network or internet
- Humidification and air purification in one; covers large spaces up to 96 m²
- Intuitive display design with coloured Daikin Eye, visual way of informing users about indoor air quality
- Pure air thanks to Daikin's 'Catch and Clean' approach in decomposing harmful substances
- High performance electrostatic HEPA filter with no need to change for 10 years
- Whisper Quiet operation (down to 18 dB(A))

Sensors

Dust (PM2.5/dust) sensor	•
Odour sensor	•
Temperature sensor	•
Humidity sensor	•

Mode

Auto fan mode	•
Anti-pollen mode	•
Turbo mode	•
Quiet mode	•
Econo mode	•
Circulation mode	•
Moist mode	•

Functions

Catch & clean	•
Deodorizing filter	•
Onecta app	•
Child proof lock	•
Brightness adjustment	•
Auto restart after power failure	•



Specifications



Onecta app

Flash Streamer

MCK70ZBFW

MCK70ZBFH

MCK70ZW

MCK70ZH

Indoor Unit				70ZW/70ZBFW	70ZH/70ZBFH
Applicable room area			m ²	48(1)/96(2)	
CADR			m ²	375	
Weight	Unit		kg	12.5	
Dimensions	Unit	HeightxWidthxDepth	mm	760x315x315	
Colour				White	Gray
Air flow rate		Air purifying operation	Silent/Low/Medium/Turbo	m ³ /h	84/132/210/420
		Humidifying operation	Silent/Low/Medium/Turbo	m ³ /h	84/132/210/420
Sound pressure level	Air purifying operation	Silent/Low/Medium/Turbo		dBA	18/27/37/54
	Humidifying operation	Silent/Low/Medium/Turbo		dBA	18/27/37/54
Humidifying operation	Power input	Silent/L/M/Turbo		kW	0.010/0.012/0.023/0.084
	Humidification	Turbo		ml/h	700
	Water tank capacity			l	3.4
Air purifying operation	Power input	Silent/L/M/Turbo		kW	0.010/0.011/0.020/0.082
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/60/220-240/220-230

(1)The coverage area is appropriate for operating the unit of maximum fan speed (HH). Coverage area indicates the space where a certain amount of dust particles can be removed in 30 minutes. (2)Converted to NRCC standards from test values in accordance with JEM1467. | Converted to CADR standards from test values in accordance with JEM1467. | Humidification amount changes in accordance with indoor and outdoor temperature and humidity. Measurement condition: 20°C in temperature, 30% in humidity. | Operating sound levels are the average of values measured at 1m away from the front, left, right and top of the unit. (These are equal to the values in an anechoic chamber) | Electrostatic HEPA filter and humidifying filters are attached in the unit. | Requirements according to JEM1467. | "HI" is displayed when the PM2.5 concentration exceeds 99µg/m³.